

SL1

SL2

SP1

SP2



Specifications

Current rating	1 A
Insulation resistance	1000 MΩ min.
Withstanding voltage	500 V AC
Operating temperature	- 40°C to +105°C
Contact material (RoHS compliant)	Copper Alloy
Insulator material (RoHS compliant)	PA6T UL 94 V-0

PCB Hole Layout

single row

dual row

**How to order**S xx - xxx - S xxx/xx - 55/1

Rows single plastic	Nbr of pins	Pin code	DIM “A”	DIM “B”	Plating	
L1 = single row	single row = 003 to 050	079/01	2.80 mm	2.60 mm	55 = Gold	
L2 = dual row	dual row = 006 to 100	091/02	4.00 mm	2.60 mm		
		111/01	6.00 mm	2.60 mm		
		164/01	2.50 mm	11.40 mm		
		179/01	12.30 mm	3.10 mm		
		other dimensions on request				
Rows Boardspacer	Nbr of pins	Pin code	DIM “A”	DIM “B”	DIM “C”	
P1 = single row	single row = 003 to 050	084/01	1.10 mm	1.30 mm	6.00 mm	other platings on request
P2 = dual row	dual row = 006 to 100	116/01	2.80 mm	2.60 mm	6.20 mm	
		152/01	6.00 mm	3.00 mm	6.20 mm	
		127/01	2.20 mm	2.20 mm	8.30 mm	
		137/01	3.00 mm	2.30 mm	8.40 mm	
		160/06	3.00 mm	4.00 mm	9.00 mm	
		210/06	5.50 mm	2.50 mm	13.00 mm	
		218/01	6.00 mm	1.80 mm	14.00 mm	
		other dimensions on request				